


<div></div>																
<table><tr><td>Width (B)</td><td>51 mm</td></tr><tr><td>Width (C)</td><td>35 mm</td></tr><tr><td>Width Total (T)</td><td>56.5 mm</td></tr><tr><td>Brand</td><td>FAG</td></tr><tr><td>Dynamic Load(Cr)</td><td>101164.02 lbs</td></tr><tr><td>Speed Limit (RPM)</td><td>3850</td></tr></table>		Width (B)	51 mm	Width (C)	35 mm	Width Total (T)	56.5 mm	Brand	FAG	Dynamic Load(Cr)	101164.02 lbs	Speed Limit (RPM)	3850	<div></div>		
Width (B)	51 mm															
Width (C)	35 mm															
Width Total (T)	56.5 mm															
Brand	FAG															
Dynamic Load(Cr)	101164.02 lbs															
Speed Limit (RPM)	3850															
		COMPONENT														
	<p>Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com</p>	<p>This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.</p>	31320-X-XL		UNIT											
			FAG													
			Fag, Tapered Roller Bearing, Tapered Roller Bearings 313. M		SHEET											