

<table><tr><td>Width (B)</td><td>12 mm</td></tr><tr><td>Contact Angle</td><td>25° contact angle</td></tr><tr><td>Bearing Arrangement</td><td>Pair - Back-to-Back</td></tr><tr><td>Brand</td><td>SKF</td></tr><tr><td>Precision</td><td>P4A</td></tr><tr><td>Ring Material</td><td>Chrome Steel 100Cr6</td></tr><tr><td>Ball Material</td><td>Chrome Steel 100Cr6</td></tr><tr><td>Preload</td><td>Extra Light Preload</td></tr><tr><td>Dynamic Load(Cr)</td><td>881 lbs</td></tr></table>		Width (B)	12 mm	Contact Angle	25° contact angle	Bearing Arrangement	Pair - Back-to-Back	Brand	SKF	Precision	P4A	Ring Material	Chrome Steel 100Cr6	Ball Material	Chrome Steel 100Cr6	Preload	Extra Light Preload	Dynamic Load(Cr)	881 lbs		
Width (B)	12 mm																				
Contact Angle	25° contact angle																				
Bearing Arrangement	Pair - Back-to-Back																				
Brand	SKF																				
Precision	P4A																				
Ring Material	Chrome Steel 100Cr6																				
Ball Material	Chrome Steel 100Cr6																				
Preload	Extra Light Preload																				
Dynamic Load(Cr)	881 lbs																				
		COMPONENT																			
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	71900 ACD/P4ADBA SKF 10mm X 22mm X 12mm, Super Precision, Angular Contact Bearing, 25° Contact Angle, Pair - Back-to-back	UNIT																	
				SHEET																	