


<div>✖</div>																	
<table><tr><td>Inner Ring Bore (d)</td><td>10 mm</td></tr><tr><td>Outer Ring O.D. (D)</td><td>27 mm</td></tr><tr><td>Height (H)</td><td>3.2 mm</td></tr><tr><td>Load Rating (Ca)</td><td>2068.24 lbs</td></tr><tr><td>Load Rating (Coa)</td><td>5732.63 lbs</td></tr><tr><td>Max Speed Greasex100</td><td>16900</td></tr><tr><td>Brand</td><td>INA</td></tr></table>		Inner Ring Bore (d)	10 mm	Outer Ring O.D. (D)	27 mm	Height (H)	3.2 mm	Load Rating (Ca)	2068.24 lbs	Load Rating (Coa)	5732.63 lbs	Max Speed Greasex100	16900	Brand	INA	<div>✖</div>	
Inner Ring Bore (d)	10 mm																
Outer Ring O.D. (D)	27 mm																
Height (H)	3.2 mm																
Load Rating (Ca)	2068.24 lbs																
Load Rating (Coa)	5732.63 lbs																
Max Speed Greasex100	16900																
Brand	INA																
		COMPONENT															
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	UNIT														
			SHEET														
		AXW10 INA Axial Needle Roller Bearing, Axial Needle Roller Bearings.															