

<table><tr><td>Width (B)</td><td>18 mm</td></tr><tr><td>Brand</td><td>INA</td></tr><tr><td>Dynamic Load(Cr)</td><td>2787.63 lbs</td></tr><tr><td>Dynamic Load AxialCA</td><td>708.15 lbs</td></tr><tr><td>Static Load Axial ca</td><td>1101.56 lbs</td></tr><tr><td>Speed Limit (RPM)</td><td>20600</td></tr><tr><td>Reference Speed</td><td>15000</td></tr></table>		Width (B)	18 mm	Brand	INA	Dynamic Load(Cr)	2787.63 lbs	Dynamic Load AxialCA	708.15 lbs	Static Load Axial ca	1101.56 lbs	Speed Limit (RPM)	20600	Reference Speed	15000		
Width (B)	18 mm																
Brand	INA																
Dynamic Load(Cr)	2787.63 lbs																
Dynamic Load AxialCA	708.15 lbs																
Static Load Axial ca	1101.56 lbs																
Speed Limit (RPM)	20600																
Reference Speed	15000																
		COMPONENT															
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	NKIA5903-XL	UNIT													
			INA Ina, Needle Roller/angular Contact, Nkia..-xl, Needle Roller/angular Contact														
				SHEET													