

✖																	
<table><tr><td>Width (B)</td><td>20 mm</td></tr><tr><td>Brand</td><td>INA</td></tr><tr><td>Dynamic Load(Cr)</td><td>2697.71 lbs</td></tr><tr><td>Dynamic Load AxialCA</td><td>651.95 lbs</td></tr><tr><td>Static Load Axial ca</td><td>944.2 lbs</td></tr><tr><td>Speed Limit (RPM)</td><td>21600</td></tr><tr><td>Reference Speed</td><td>17000</td></tr></table>		Width (B)	20 mm	Brand	INA	Dynamic Load(Cr)	2697.71 lbs	Dynamic Load AxialCA	651.95 lbs	Static Load Axial ca	944.2 lbs	Speed Limit (RPM)	21600	Reference Speed	17000	✖	
Width (B)	20 mm																
Brand	INA																
Dynamic Load(Cr)	2697.71 lbs																
Dynamic Load AxialCA	651.95 lbs																
Static Load Axial ca	944.2 lbs																
Speed Limit (RPM)	21600																
Reference Speed	17000																
		COMPONENT															
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	NKIB5902-XL INA Ina, Needle Roller/angular Contact, Nkib59..-xl, Needle Roller/angular Contact	UNIT													
			SHEET														