


<div>✖</div>																	
<table><tr><td>Height (H)</td><td>25 mm</td></tr><tr><td>Brand</td><td>INA</td></tr><tr><td>Dynamic Load(Cr)</td><td>3034.92 lbs</td></tr><tr><td>Dynamic Load AxialCA</td><td>3596.94 lbs</td></tr><tr><td>Static Load Axial ca</td><td>7531.1 lbs</td></tr><tr><td>Speed Rating Grease</td><td>12000</td></tr><tr><td>Speed Rating Oil</td><td>5500</td></tr></table>		Height (H)	25 mm	Brand	INA	Dynamic Load(Cr)	3034.92 lbs	Dynamic Load AxialCA	3596.94 lbs	Static Load Axial ca	7531.1 lbs	Speed Rating Grease	12000	Speed Rating Oil	5500	<div>✖</div>	
Height (H)	25 mm																
Brand	INA																
Dynamic Load(Cr)	3034.92 lbs																
Dynamic Load AxialCA	3596.94 lbs																
Static Load Axial ca	7531.1 lbs																
Speed Rating Grease	12000																
Speed Rating Oil	5500																
		COMPONENT															
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	NKXR17-Z-XL INA Ina, Needle Roller/axial Cylindrica, Nkxr..-z-xl, Needle Roller/axial Cylindrica														
			UNIT														
			SHEET														