

<table><tr><td>Width (B)</td><td>40 mm</td></tr><tr><td>Contact Angle</td><td>25° contact angle</td></tr><tr><td>Bearing Arrangement</td><td>Pair - Back-to-Back</td></tr><tr><td>Brand</td><td>SKF</td></tr><tr><td>Precision</td><td>P4A</td></tr><tr><td>Ring Material</td><td>Chrome Steel 100Cr6</td></tr><tr><td>Ball Material</td><td>Chrome Steel 100Cr6</td></tr><tr><td>Preload</td><td>Extra Light Preload</td></tr><tr><td>Dynamic Load(Cr)</td><td>20831 lbs</td></tr><tr><td>Closure</td><td>Rubber Seal</td></tr></table>		Width (B)	40 mm	Contact Angle	25° contact angle	Bearing Arrangement	Pair - Back-to-Back	Brand	SKF	Precision	P4A	Ring Material	Chrome Steel 100Cr6	Ball Material	Chrome Steel 100Cr6	Preload	Extra Light Preload	Dynamic Load(Cr)	20831 lbs	Closure	Rubber Seal		
Width (B)	40 mm																						
Contact Angle	25° contact angle																						
Bearing Arrangement	Pair - Back-to-Back																						
Brand	SKF																						
Precision	P4A																						
Ring Material	Chrome Steel 100Cr6																						
Ball Material	Chrome Steel 100Cr6																						
Preload	Extra Light Preload																						
Dynamic Load(Cr)	20831 lbs																						
Closure	Rubber Seal																						
		COMPONENT																					
	Pacific International Bearing, Inc. 33258 Central Ave, Union City, CA 94587 1-800-228-8895, 510-512-7000, info@pibsales.com www.pibsales.com	This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.	S71920 ACD/P4ADBA SKF 100mm X 140mm X 40mm, Super Precision, Angular Contact Bearing, 25° Contact Angle, Pair - Back-to-back	UNIT																			
				SHEET																			